

M2K30-NW2

Cut Resistance Plus Heat Protection



APPLICATIONS

- Metal Fabrication
- Plastics Manufacturing
- Glass Handling
- High Conductive Heat Areas
- Low Temperature Environments
- General Purpose

FEATURES



High heat glove; Withstood time to pain of 12.5 seconds at 608°F

Temperature noted is dependent upon duration, application, and environment. Actual use temperature may be lower.

With a conductive heat resistance of 608° F intermittent, the M2K30-NW2 provides high heat protection in a cut-resistant, seamless knit glove. Our glove-within-a-glove design helps trap air in between layers, making it a good choice for applications where the wearer may come into direct contact with hot objects. A high temperature resistant nitrile coating is applied to the glove to provide a sure grip. 100% made in the USA.



ATTRIBUTES

STYLE	Seamless Knit
GAUGE	7 g. glove in a glove (Ultra heavy weight)
ANSI CUT	A3
SIZES	S / M / L / XL
FIBER CONTENT	Outer: 100% Kevlar® Inner: Cotton / Poly
COLORS	Yellow
CARE	Machine wash or dry clean
PACKAGING	6 Dz. per case

PRODUCT NO.

SIZE



M2K30-NW2-S	Small	Light Blue
M2K30-NW2-M	Medium	Green
M2K30-NW2-L	Large	White
M2K30-NW2-XL	Extra Large	Black